

MCRT[®] 48550V & 48551V Non-Contact DC OPERATED TORQUEMETERS

With Spline Drive per AND 10262 & AND 20002

CE



- ✓ Hardened to EMI From Adjustable Speed Drives
- ✓ Dual ± 5 Volt Outputs
- ✓ Single Supply Operation
- ✓ Corrosion Resistant
- ✓ Ferrite-free Rotary Transformer
- ✓ Remote, NIST Traceable Cal*

Interface Directly To PC and PLC Controllers and Data Acquisition Systems

*NIST traceable calibration performed in our accredited laboratory (NVLAP Lab Code 200487-0). For details visit www.himmelstein.com or follow the accreditation link at www.nist.gov

Description

When installed between a driver and load, MCRT[®] 48550V/48551V sensors *measure static and dynamic shaft torque and speed* (an option). A strain gaged, 15-5 PH stainless shaft senses torque and cancels bending and thrust. *Robust, ferrite-free rotary transformers* connect torque sensing gages to an *integral, noise immune, carrier amplifier*. Rotary transformers don't generate noise or wear, and are immune to vibration, lubricants and other hostile environments. Unlike ferrite transformers, Himmelstein ferrite-free units aren't susceptible to cracking and impact induced damage.

These torque meters mate with and support test components meeting the specified spline standards; see overleaf. Their overload torque rating is twice the full scale range. Standard models operate from stall to $\pm 15,000$ rpm; higher speed versions can be supplied on special order – if higher speeds are needed, please consult the factory. Both standard and zero velocity speed pickups are optional. *All versions incorporate advanced, noise reduction technology that hardens these sensors to EMI generated by IGBT-based adjustable speed drives (ASD's).*

MCRT [®] Model	Torque Range (lb-in)	Torque Overload (lb-in)	Max Speed (rpm)	Stiffness ¹ (lb-in/radian)	Inertia ¹ (oz-in sec ²)	Max. Wt. (lbs.)
48550V(5-1)	50	100	0 to $\pm 15,000$	5,570	0.15	13
48550V(1-2)	100	200	0 to $\pm 15,000$	15,000	0.15	13
48550V(2-2)	200	400	0 to $\pm 15,000$	54,500	0.15	13
48550V(5-2)	500	1,000	0 to $\pm 15,000$	94,500	0.15	13
48550V(1-3)	1,000	2,000	0 to $\pm 15,000$	145,000	0.15	13
48551V(1-3)	1,000	2,000	0 to $\pm 10,000$	247,000	0.16	14
48551V(2-3)	2,000	4,000	0 to $\pm 10,000$	428,000	0.16	14
48551V(5-3)	5,000	10,000	0 to $\pm 10,000$	486,000	0.16	14
48551V(1-4)	10,000	20,000	0 to $\pm 10,000$	613,000	0.17	14

1. Both stiffness and inertia are conservatively rated from shaft end-to-end.

S. HIMMELSTEIN AND COMPANY

2490 Pembroke Avenue, Hoffman Estates, IL 60169, USA • Tel: 847/843-3300 • Fax: 847/843-8488

General Specifications

Nonlinearity¹ (% of Rating): = < ±0.15
Hysteresis (% of Rating): = < ±0.15
Nonrepeatability (% of Rating): = < ±0.07
Accuracy (combined nonlinearity, hysteresis and non-repeatability, % of Rating): = < ±0.2
Rotational Effect on Zero (% of Rating): = < ±0.10
Temperature Effects:
 Zero (% of Rating/degree F.): = < ±0.003
 Span (% of Reading/degree F.): = < ±0.003
 Compensated Range: +75 to +175 deg. F.
 Minimum Usable Range: -25 to +185 deg. F.
 Storage Range: -65 to +225 deg. F.

Remote Calibration Accuracy (% of Rating @ 75 deg. F.): .. = < ±0.10
Outputs: Fully bidirectional, dual outputs, as follows
 Clockwise (CW) Torque: +5 Volts
 Counterclockwise (CCW) Torque: -5 Volts
 Minimum Resistive Load: 10kΩ
 Maximum Capacitive Load: 0.05uF
 Nominal Overrange: ±33% of Rating
 Bandwidth: High Frequency Output \approx dc to 500 Hz.
 Low Frequency Output \approx dc to 1 Hz.
Zero Balance (% of Rating): = < ±1%
Input Power: 10.5 to 24 Volts dc @ 90 mA, nominal.
Power Supply Effect: <0.01% of Full Scale per Volt.
Optional Speed Pickups³: Two types produce 60 pulses/revolution.
 Option A is the Standard Type and Option Z is the Zero Velocity Type.

Notes

1. Based on end point method.
2. Electrical outputs remain *linear* to the *overrange* level. A torquemeter won't *yield* below its rated *overload* torque. Reserve the region between rated and overload torques for unexpected loads; see Bulletin 705.
3. If speed is ≤100 rpm and/or if high electrical noise is present, use Option Z. Speed ratings are for continuous, bi-directional operation.
4. These torquemeters operate in a condensing atmosphere, and if wetted with non-corrosive fluids and mud. When used under contaminated conditions, clean regularly or cover to deflect contaminants. They are not submersible.
5. Specifications are subject to change without notice.

Order Number	MCRT[®] 48550V	(1-2)	NN	Z
	<i>Model Number</i>	<i>Range</i>	<i>Required Double NN Designator</i>	<i>Speed Pickup: use A for Standard, use Z for Zero Velocity, use N for None.</i>
An MCRT [®] 48550V(1-2)NNZ is a 100 lb-in version with a Zero Velocity speed pickup.				

Dimensional Data

Model Number	Torque Range	Maximum Overhung Moment (WxD)	Spline Data	Dimension L (inch)
MCRT [®] 48550V	All	2,000 lb-in	16 teeth, 20/30 D.P.	8 17/32
MCRT [®] 48551V	All	2,000 lb-in	24 teeth, 20/30 D.P.	9 3/32

